

FORMULA X-TREME ULTRA HIGH PERFORMANCE STRIPPER

1. IDENTIFICATION OF THE MIXTURE (PREPARATION) AND OF THE COMPANY/UNDERTAKING

1.1 PRODUCT IDENTIFIER

Product Name: Formula X-Treme UHP Stripper

Product Number: 549

1.2 RELEVANT IDENTIFIED USES OF THE MIXTURE AND USES ADVISED AGAINST

Product intended for commercial and industrial use only.

Intended Use: Floor Finish remover concentrate

Uses Advised Against: Other than per labelled instructions.

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Importer:

Eclipse Floor Solutions Pty Ltd

41-43 Steel Street

Capalaba

Queensland 4157

Telephone: (07) 3390 3027

Email: info@eclipsefloorsolutions.com.au

Internet: www.eclipsefloorsolutions.com.au

1.4 EMERGENCY TELEPHONE NUMBER

For Chemical Emergency: Spill, Leak, Fire, Exposure or Accident Call:

The Australian Poisons Information Hotline All States 24 Hour Ph: 13 11 26

2. HAZARDS IDENTIFICATION

2.1 CLASSIFICATION OF THE MIXTURE (PREPARATION)

This mixture has been classified according to EC 1272/2008.

CLP Classification: Acute Toxicity (Oral) - Category 4
Skin Corrosion - Category 1B
Eye Damage - Category 1
Acute Toxicity (Inhalation) - Category 4

2.2 LABEL ELEMENTS

Signal Word: Danger

Hazard pictogram(s):



Hazard Statement(s):

H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H318 Causes serious eye damage.
H332 Harmful if inhaled

Precautionary Statement(s):

P260 Do not breathe mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection.
P310 Immediately call a POISON CENTER/doctor if you feel unwell.
P301+330+331+311 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER/doctor.

P303+361+353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3 OTHER HAZARDS

No other hazards are known to the supplier

**SAFETY DATA SHEET**

Conforms to 1907/2006/EC - (EU) 453/2010

Issued: Aug. 27, 2015

Supersedes: May 20, 2015

FORMULA X-TREME ULTRA HIGH PERFORMANCE STRIPPER**3. COMPOSITION/INFORMATION ON INGREDIENTS****3.1/3.2 SUBSTANCES/MIXTURES**

Ingredient	EC No.	Weight %	CAS No.	CLP Classification	
				Hazard Class	Hazard Statement(s)*
ethylene glycol monobutyl ether	203-905-0	30 - 45	111-76-2	Acute Tox 4 Eye Irrit 2 Skin Irrit 2	H302, H312, H332 H319
benzyl alcohol	202-859-9	20 - 30	100-51-6	Acute Tox 4	H302,H332
ethanolamine	205-483-3	15 - 25	141-43-5	Acute Tox 4 Skin Corr 1B STOT SE 3	H302,H312,H332 H314 H335

*See section 16 for the full text of R phrases and Hazard Statements

4 FIRST AID MEASURES**4.1 DECIPTION OF FIRST AID MEASURES**

- Eye Contact:** Immediately wash out with water for at least 15 minutes. (If easy to do, remove contact lenses, if worn.) Seek medical attention immediately.
- Skin Contact:** Immediately wash with plenty of water for at least 15 minutes. (Remove any contaminated clothing and shoes.) Seek medical attention immediately.
- Inhalation:** If breathing is difficult: Remove to fresh air. Seek medical attention immediately.
- Ingestion:** Call a physician or poison control center immediately. DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

- Eye Contact:** Harmful in contact with eyes. May cause permanent damage.
- Skin Contact:** Harmful in contact with skin. May cause permanent damage.
- Inhalation:** May be harmful if inhaled. May cause irritation and corrosive effects to nose, throat and respiratory tract.
- Ingestion:** Harmful if swallowed. May cause burns to mouth, throat and stomach.

4.3 INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

No information available.

5. FIRE FIGHTING MEASURES**5.1 EXTINGUISHING MEDIA**

In case of fire: use dry chemical, water spray, foam, carbon dioxide

5.2 SPECIAL HAZARDS ARISING FROM THE MIXTURE

Hazardous combustion products: None known

5.3 ADVICE FOR FIRE FIGHTERS

As in any fire, wear self contained breathing apparatus and suitable protective clothing including gloves and eye/face protection. Fire-fighters should wear clothing conforming to EN469 for chemical incidents. Materials can splatter above 100°C/212°F. Corrosive material.

6. ACCIDENTAL RELEASE MEASURES**6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES**

Refer to Section 8 for appropriate personal protective equipment.

6.2 ENVIRONMENTAL PRECAUTIONS

Keep spills and cleaning runoff out of sewers and open bodies of water.

6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

Small spills: Absorb spill on inert material (e.g. sand, earth) and dispose of as waste material in accordance with national and regional provisions.



SAFETY DATA SHEET

Conforms to 1907/2006/EC - (EU) 453/2010

Issued: Aug. 27, 2015

Supersedes: May 20, 2015

FORMULA X-TREME ULTRA HIGH PERFORMANCE STRIPPER

Large spills: Keep spectators away. Floors may be slippery; use care to avoid falling. Neutralize spill area. Dike and contain spill with inert material (e.g. sand, earth). Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for disposal.

6.4 REFERENCE TO OTHER SECTIONS: Refer to Section 8 of the SDS.

7. HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Use only in well-ventilated areas. Avoid breathing vapours or spray mists. Remove and wash contaminated clothing and footwear before re-use.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage temperature (Max. 60°C/140°F) (Min. 1°C/34°F). Keep from freezing. Keep container sealed when not in use. Keep out of reach of children.

7.3 SPECIFIC END USE(S): No information available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS

Workplace Exposure Limits:

Ingredient	Source	TWA (8hours)		STEL (Short term)		Note(s)
		ppm	mg/m ³	ppm	mg/m ³	
ethylene glycol monobutyl ether	ACGIH TLV	20	97	-	-	BEI
	DE (TRGS 900)	-	-	10	49	H,Y, AGS
	DK - At-Vejledning Stoffer og materialier- C.0.1	20	98	-	-	EH
	EU (2000/39/EC)	20	98	50	246	Skin
	NO – Forskrift, best.nr. 704	-	-	10	50	H
	EH40	25	123	50	246	Sk, BMGV

Ingredient	Source	TWA (8hours)		STEL (Short term)		Note(s)
		ppm	mg/m ³	ppm	mg/m ³	
ethanolamine	ACGIH TLV	3	7.5	6	15	-
	DE (TRGS 900)	-	-	2	5.1	H,Y,Sh
	DK - At-Vejledning Stoffer og materialier- C.0.1	1	2.5	-	-	H
	EU (2006/15/EC)	1	2.5	3	7.6	Skin
	NO Administrative Norm	1	2.5	-	-	H
	EH40	1	2.5	3	7.6	Skin

8.2 EXPOSURE CONTROLS

Engineering Controls: Use only with adequate ventilation. Use local ventilation and other engineering controls to maintain airborne contaminants below established and recommended exposure limits. If this product contains ingredients with exposure limits, monitoring may be required to determine the effectiveness of ventilation and other control measures.

Environmental exposure controls: No specific environmental exposure controls known.

Personal Protective Equipment (PPE)

Eye/Face Protection: Safety eyewear is recommended to avoid chemical splashes and mists. Safety glasses or goggles (EN166).

Hand Protection: Chemical resistant gloves are recommended. (EN374).
Protective index 6, Breakthrough time > 480 mins. (E.g. - nitrile gloves, 0.4 mm thickness)
Protective gloves should be selected according to the application and duration of use. Workplace selection should take into consideration handling requirements, physical requirements and exposure to other substances.

Skin Protection: If major exposure is possible, wear suitable protection such as rubber boots, apron, etc.

**SAFETY DATA SHEET**

Conforms to 1907/2006/EC - (EU) 453/2010

Issued: Aug. 27, 2015

Supersedes: May 20, 2015

FORMULA X-TREME ULTRA HIGH PERFORMANCE STRIPPER

Respiratory Protection: Respiratory protection should be worn when there is a potential of inadequate ventilation. If exposure limits are exceeded or symptoms are experienced, use an approved respirator with multi-purpose combination filter. (E.g. - EN 14387- ABEK)

9. PHYSICAL AND CHEMICAL PROPERTIES**9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES**

Appearance: clear, colorless liquid
Odor: butyl odor
Odor Threshold: data not available
pH: 11.5
Freezing Point: data not available
Initial boiling point/boiling range: data not available
Flash Point: > 77°C
Evaporation Rate: data not available
Upper/lower flammability/explosive limits: data not available
Vapor Pressure: data not available
Vapor Density: data not available
Relative Density: 0.98 kg/L @ 20°C
Solubility: miscible in water
Partition Coefficient (n-octanol/water): data not available
Auto Ignition temperature: data not available
Decomposition Temperature: data not available
Viscosity: < 20 centipoise @ 20°C
Explosive Properties: none
Oxidizing properties: none

9.2 OTHER INFORMATION

VOC: 60% (as supplied), 2.8% (1:20), 1.9% (1:30), 1.43% (1:40)

10. STABILITY AND REACTIVITY

10.1 REACTIVITY: None known
10.2 CHEMICAL STABILITY: Stable under normal conditions.
10.3 POSSIBILITY OF HAZARDOUS REACTIONS: Product may react strongly with water. Care should be used if diluting; product should be slowly added to water.
10.4 CONDITIONS TO AVOID: None known
10.5 INCOMPATIBLE MATERIALS: Strong acids, bases and oxidizing agents.
10.6 HAZARDOUS DECOMPOSITION PRODUCTS: None known

11. TOXICOLOGICAL INFORMATION**11.1 INFORMATION ON TOXICOLOGICAL EFFECTS**

ACUTE TOXICITY: Toxicity testing has not been completed on the mixture.
Classified as Acute Toxicity (Oral) - Category 4
Classified as Acute Toxicity (Inhalation) - Category 4

Component	CAS #	LD50 Oral-Rat (mg/kg)	LD50 Dermal - (mg/kg)	LC50 Inhalation- (mg/l)
ethylene glycol monobutyl ether	111-76-2	470 - 1746	guinea pig, >2000	guinea pig (1hr), >3.1
benzyl alcohol	100-51-6	1230	rabbit, 2000 mg/kg	(4hr), 8.9
ethanolamine	141-43-5	1090 - 3320	rat, 2504	rat (4hr), >1.48

SKIN CORROSION/IRRITATION: Classified as Skin Corrosive - Category 1B

SERIOUS EYE DAMAGE/IRRITATION: Classified as Eye Damage - Category 1

RESPIRATORY OR SKIN SENSITIZATION: Based on available data, the classification criteria are not met.



SAFETY DATA SHEET

Conforms to 1907/2006/EC - (EU) 453/2010

Issued: Aug. 27, 2015

Supersedes: May 20, 2015

FORMULA X-TREME ULTRA HIGH PERFORMANCE STRIPPER

GERM CELL MUTAGENICITY:	Based on available data, the classification criteria are not met.
CARCINOGENICITY:	Based on available data, the classification criteria are not met.
REPRODUCTIVE TOXICITY:	Based on available data, the classification criteria are not met.
STOT-SINGLE EXPOSURE:	Based on available data, the classification criteria are not met.
STOT-REPEATED EXPOSURE:	Based on available data, the classification criteria are not met.
ASPIRATION HAZARD:	Based on available data, the classification criteria are not met.

12. ECOLOGICAL INFORMATION

12.1 TOXICITY: Ecological testing has not been completed on the mixture.

Component	CAS #	LC50 - 96 hr	LC50 - 48 hr	EC50 - 72 hr
ethylene glycol monobutyl ether	111-76-2	vertebrate, 820-1490 mg/ml	Daphnia magna, 835 mg/l	algae, 911 mg/l
benzyl alcohol	100-51-6	vertebrate, 770 mg/ml	Daphnia magna, 400 mg/l	algae, 640 mg/l
ethanolamine	141-43-5	vertebrate, 125-2010 mg/ml	Daphnia magna, 33-93 mg/l	algae, 2.5 mg/l

12.2 PERSISTENCE AND DEGRADABILITY: No data available.

Component	CAS #	Biodegradation
ethylene glycol monobutyl ether	111-76-2	readily biodegradable
benzyl alcohol	100-51-6	readily biodegradable
ethanolamine	141-43-5	readily biodegradable

12.3 BIOACCUMULATIVE POTENTIAL: No data available.

Component	CAS #	Partition coefficient n-octanol/water (Log Kow)	Bioconcentration factor (BCF)
ethylene glycol monobutyl ether	111-76-2	0.81	< 100
benzyl alcohol	100-51-6	not available	<100
ethanolamine	141-43-5	-1.91	< 100

12.4 MOBILITY IN SOIL: No data available.

Component	CAS #	Soil Organic Carbon-Water Partitioning Coefficient (Koc)
ethylene glycol monobutyl ether	111-76-2	67
benzyl alcohol	100-51-6	not available
ethanolamine	141-43-5	1.17

12.5 RESULTS OF PBT AND vPvB ASSESSMENT: No data available.

12.6 OTHER ADVERSE EFFECTS: No data available.

12.7 ADDITIONAL INFORMATION: No data available.

13. DISPOSAL CONSIDERATIONS

13.1 WASTE TREATMENT METHODS

Disposal of this material should be in accordance with local, regional and national regulations.
EU Waste Catalogue: 20 01 15*

14. TRANSPORT INFORMATION

14.1 UN NUMBER:	UN1760
14.2 UN PROPER SHIPPING NAME:	Corrosive liquid, n.o.s. (ethanolamine)
14.3 TRANSPORT HAZARD CLASSES:	8

**SAFETY DATA SHEET**

Conforms to 1907/2006/EC - (EU) 453/2010

Issued: Aug. 27, 2015

Supersedes: May 20, 2015

FORMULA X-TREME ULTRA HIGH PERFORMANCE STRIPPER

14.4 PACKING GROUP: II
14.5 ENVIRONMENTAL HAZARDS: N/A

14.6 SPECIAL PRECAUTIONS FOR USER:
Package volumes < 1 L are shipped as Limited Quantity; as permitted by hazard class and quantity limits.

IMDG

Emergency Schedules (EmS): Fire F-A, Spillage S-B
Stowage and Segregation: Category B. Clear of living quarters.
Marine Pollutant: None

ADR/RID

Class: 8
Item Number: 80
Classification Code: C9

14.7 TRANSPORT IN BULK ACCORDING TO ANNEX II OF MAPROL73/78 AND THE IBC CODE: N/A

15. REGULATORY INFORMATION**15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE MIXTURE**

EINECS STATUS: Ingredients are included in the EINECS/ELINCS/NLP inventories.
NATIONAL REGULATIONS: No additional national regulations are known to the supplier.

15.2 CHEMICAL SAFETY ASSESSMENT: No information available.

16. OTHER INFORMATION**REVISION INFORMATION:**

Aug. 27, 2015 - Revisions Section 2, 3, 16 (remove DPD reference), Section 2 (Classification, Hazard Statements), Section 3 (Weight %), Section 5, 8 (additional details), Section 9 (flash point)

ABBREVIATIONS:

N/A - Not applicable
N/E - Not Established
N/L - Not Listed

FULL TEXT OF HAZARD STATEMENTS:

H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.

FULL TEXT OF PRECAUTIONARY STATEMENTS:

P261 Avoid breathing mist/vapours/spray.
P264 Wash thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P310 Immediately call a POISON CENTER/doctor.
P321 Specific treatment (see ... on this label).
P337+313 If eye irritation persists: Get medical advice/attention.
P363 Wash contaminated clothing before reuse.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulation.

ISSUED BY:

Eclipse Floor Solutions Pty Ltd